

Specifications

ENGINE	
Displacement	249.4cc
Type	4-Stroke
Cooling	Water-Cooled
Bore and Stroke	71 x 63 mm
Max. HP	13.2 KW / 7000 rpm
Max. Torque	20.6 Nm / 5500 rpm
Transmission	Automatic CVT with Reverse Gear
Compression Ratio	10.5 : 1
SUSPENSION	
Front Suspension	Double A-arm
Rear Suspension	Swing Arm
BRAKES	
Front & Rear Brake	Hydraulic Disc
Foot Brake	All Wheels Stop by Foot Pedal
Parking Brake	Mechanical Lock of The Lever
TIRES	
Front Tire	22 x 7 - 12 (on-road)
Rear Tire	22 x 10 - 12 (on-road)
RIMS	
Front Rim	Aluminum Alloy Rims 12" x 6" (ET +15)
Rear Rim	Aluminum Alloy Rims 12" x 7.5" (ET -35)
DIMENSIONS	
Wheelbase	1250 mm
Wheel Tread (Front / Rear)	970mm / 890mm
Length x Width x Height	2030 mm x 1150 mm x 1165 mm
Seat Height	820 mm
Dry Weight	200 kgs



MAGMAX

275

--RACING-Styling ATV--



We Listen to Customers.
www.aiemotor.com

Headquarter:

No. 15, Lane 315, Hsin-Shu Rd,
Hsin Chuang City, Taipei, Taiwan

TEL: 886-2-22068043
FAX: 886-2-22081039

Factory:

Lot VIII-1, Ho Nai Industrial Zone,
Thong Nhat Dist, Dong Nai Province, Viet Nam

TEL: 84-61-981708
FAX: 84-61-982932



Wider Wheel Tread For Better Handling Stability



Unique Racing Tires With 12" Alloy Rims

RPM Meter, Trip Meter, Fuel Gauge, And Power Socket

Key-Operated Storage Compartment

Two-Seaters With Full Length Floorboard

Innovative Twin Mufflers To Increase Power

